



KEIM Romanit-KSP

## DECLARATION OF PERFORMANCE

Number of the declaration of performance and unique identification of the product-type  
**01 0033**

Intended use  
**Plaster for use as interior plaster  
for walls, ceilings, pillars and partition walls**

Manufacturer  
**KEIMFARBEN GMBH, Keimstraße 16, D-86420 Diedorf**

System of AVCP  
**System 3 (reaction to fire)  
System 4 (other essential characteristics)**

Harmonised standard  
**EN 998-1:2016**

Notified body (testing institute)  
**Technische Universität München, Holzforschung München (0797)**  
performed the product type test regarding the fire behaviour according to system 3.

Declared performance

Essential characteristics	Performance
Reaction to fire	A1
Water absorption	W <sub>c</sub> 0
Water vapor permeability	$\mu \leq 15$
Tensile adhesive strength	$\geq 0,08 \text{ N/mm}^2$ (at fracture pattern A, B or C)
Thermal conductivity (Tabular values)	$\lambda_{10, \text{dry, mat}} \leq 0,82 \text{ W/(mK)}$ for P= 50 % $\lambda_{10, \text{dry, mat}} \leq 0,89 \text{ W/(mK)}$ for P= 90 %
Durability	NPD
Hazardous substances	NPD

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Manager of quality assurance and color metrics:

Diedorf, 03.12.2019

Keimstraße 16 / 86420 Diedorf  
Tel. +49 (0)821 4802-0  
Fax +49(0)821 4802-210

Deutsche Bank München  
IBAN DE37 7007 0010 0188 1580 00  
BIC DEUTDE33

Frederik-Ipsen-Straße 6 / 15926 Luckau  
Tel. +49(0) 35456 676-0  
Fax +49(0) 35456 676-38

Stadtparkasse Augsburg  
IBAN DE48 7205 0000 0000 3621 03  
BIC AUGSDE77XXX

p.p. Peter Jaser

www.keimfarben.de  
info@keimfarben.de

Registergericht Augsburg HRB 27263  
Geschäftsführer: Rüdiger Lugert